


AJ serie



Model	AJ 1000-12	AJ 1300-24	AJ 2100-12	AJ 2400-24	
Inverter					
Nominal battery voltage	12V	24V	12V	24V	
Input voltage range	10.5 - 16V (24V max.)	21-32V (44V max.)	10.5 - 16V (20V max.)	21-32V (40V max.)	
Continuous power @ 25°C	800VA	1000VA	2000VA	2000VA	
Power 30 min. @ 25°C	1000VA	1300VA	2100VA	2400VA	
Power 5 min. @ 25°C	1200VA	2000VA	2450VA	2800VA	
Power 5 sec. @ 25°C	2200VA	2800VA	5000VA	5200VA	
Maximum asymmetric load	500VA	600VA	1000VA	1200VA	
Max. efficiency (%)	93%	94%	92% @ 300VA	94% @ 300VA	
Cos phi max.	0.1 - 1 up to 800VA	0.1 - 1 up to 1000VA	0.1 - 1 up to 2000VA	0.1 - 1 up to 2000VA	
Detection of the load	Adjustable : 1 → 20W				
Current of short-circuit 2 sec. (exit)	10A (20A*)	13A (26A*)	26A (52A*)	30A (60A*)	
Output voltage	Sine wave 230Vac (115Vac*) 0/-10%				
Frequency	50 Hz (60Hz*) ± 0.05% (crystal controlled)				
Distortion THD (resistive load)	< 5% (@ Pnom. & Unom.)			< 3% (@ Pnom & Unom.)	
Consumption Stand-by	0.3W	0.4W	0.5W	0.4W	
Consumption «ON» no load	9.0W	10.0W	13W	18W	
Overheat protection (+/-5°C)	Shut down @ 75°C - Auto-restart @ 70°C				
Short circuit protection	Automatic disconnection with 2 time restart attempt				
Inversion of polarity protection	Protected by internal fuse 125A	Protected by internal fuse 100A	Not protected	Protected by internal fuse 150A	
Major discharge battery protection	Shut off @ 0.87 x Unom - Automatic restart @ Unom				
Cut overpressure	Shut off @ >1.33 x Unom - Automatic restart @ < Unom				
Acoustic alarm	Before low battery or overheating disconnection				
General data					
Weight	8.5 kg		19 kg	18 kg	
Dimensions	142mm x 420mm x 84mm		273mm x 396mm x 117mm		
Protection index IP	IP 30 conforms to DIN 40060		IP 20 conforms to DIN 40050		
Certification ECE-R 10 (E24)					
EC conformity	EN 61000-6-1, EN 61000-6-3, EN 55014, EN 55022, Dir. 89/336/EEC, LVD 73/23/EEC				
Operating temperature	-20°C up to +50°C				
Ventilation forced	From 45°C ± 5°C				
Acoustic level	< 45 dB (with ventilation)				
Warranty	2 years				
Approximate correction of Pnom	-1.5%/°C since +25°C				
Recommended battery capacity	> 5 x Pnom/Unom (recommended value in Ah)				
Length cables (Battery/left AC)	1.5m / 1m		1.7m / 1m		
Options					
Solar regulator	Voltage max.	AJ 1000-12-S 25V	AJ 1300-24-S 45V	AJ 2100-12-S 25V	AJ 2400-24-S 45V
	Current max.	25A		30A	
	Principle	Floating 3 stages (IU/UO)			
	Absorption voltage	14.4V	28.8V	14.4V	28.8V
	Floating voltage	13.6V	27.2V	13.6V	27.2V

* 115Vac/60Hz on request

Data may change without any notice.